

Top Wheel™



Top Wheel™

Belanger's Top Wheel delivers great cleaning performance at an unbeatable price to any new or existing car wash system. With consistent penetration the Top Wheel effectively cleans all horizontal surfaces of a vehicle including contoured hoods and roof lines. In contrast to other products available in the industry, Belanger's Top Wheel has one of the highest pivot points that insures an effective but safe vehicle wash. With its grease-free bearing and self-cleaning Neo-Tex foam material, the Top Wheel provides superior cleaning results with minimal maintenance.

- Automatically adjusts to precise vehicle contour to provide optimal cleaning of all top surfaces.
- High pivot point design safely accommodates line speeds up to 200 cars per hour with consistent reliable cleaning results.
- Grease-free bearings and lightweight, self-cleaning Neo-Tex foam material deliver minimal maintenance requirements.
- Standard rugged, honeycombed framework provides form, function, and superior durability.



Belanger Incorporated Product Specification Sheet



Belanger, Inc. reserves the right to revise specifications, features or designs, and to change or discontinue models at any time without notice or obligation.

BE 00 26

Copyright 2005
Belanger, Inc. ©

Specifications

Top Wheel™

REQUIREMENTS

Physical

Tunnel space required	114"
Unit Height	138"
Unit width	146"
Vehicle Height Clearance	90"

Utility

Electrical	3 phase, 2HP motor (optional) Retract 110 VAC for Retract Option
Hydraulic	6 GPM @ 900 PSI
Pneumatic (optional)	.3 CFM @ PSI (optional)
Water	(1) 3/4" hose @ 4 GPM @ 40PSI

