

# Uni-Arch™



## Uni-Arch™

The Uni-Arch™ is “universal” in application. You choose the application, pre-soak, rinse, wax, etc. You place the Uni-Arch™ anywhere in the tunnel that you want it, the entrance, middle or exit, double ‘em up, use them alone, it’s all up to you. Just another example of “flexible standards” from Belanger, Inc.

This arch was designed to be the most universally functioning arch in the industry. It is capable of high pressure, high volume, cooling, pre-soak, foaming, drying agent, sealer wax, polish wax, and rinsing applications.

The Uni-Arch™ is available with a stainless steel or brass fitting. The Uni-Arch™ with the stainless steel fitting is approved to operate high pressure up to 1000 psi, can operate with RO water and apply all industry approved acids and alkylines. The Uni-Arch™ with the brass fitting is approved to operate up to 150 psi and is perfect for neutral chemical application.

The Uni-Arch™ also has a unique marketing appeal which replaces the industrial look of welded and bolted metal with a soft rounded and colorful look. The Uni-Arch™ is available with blue or red colored protective foam covered to compliment your car wash marketing image.

The new Uni-Arch™ uses all current Belanger nozzle kits, including kits for pre-soak, rinse, spot free and wax applications.

- Constructed of 1 ½” schedule 40 stainless steel pipe
- Steel is foam covered in high quality, UV protective, 4 3/8” OD foam.
- Nozzle holes are drilled and tapped for a 1/4” npt thread



### Belanger Incorporated Product Specification Sheet



Belanger, Inc. reserves the right to revise specifications, features or designs, and to change or discontinue models at any time without notice or obligation.

BE 00 26

Copyright 2001  
Belanger, Inc. ©

# Specifications

## Uni-Arch™

### REQUIREMENTS

#### *Physical*

Vehicle clearance height	90" (228.6 cm)
Vehicle clearance width	123" (312.4 cm)
Tunnel space required	8" (20.3 cm)
Unit height	104" (264.2 cm)
Unit width	144" (365.8 cm)

#### *Utility*

Electrical	110 VAC
Water	3/4" (1.9 cm) barbed hoses fitting, 3/4 NPT, 1-1/2 NPT feed (All included)

